



AT72XUSB

DVB-C Annex B (Cable TV) Receiver, TS Recorder with DVB-C to DVB-ASI Converter Function



Standard Features:

- Combined DVB-C Annex B Input and DVB-ASI Output Device.
- High Speed USB 2.0
- Windows 2000 & XP Drivers & API.
- Accompanied by DVStation2 Alitronika's Application Software.

Input


- DVB-Cable TV Compliant QAM & 8-VSB Reception.
- Input Frequency Range: 54 MHz to 864 MHz.
- Channel Bandwidth: 6 MHz.
- Supports 188, 204 Transport Packet Sizes.

Output

- DVB-ASI According to Standard A1010 Rev1 and EN50083.



Block Diagram:



AT72XUSB

DVB-C Annex B (Cable TV) Receiver, TS Recorder with DVB-C to DVB-ASI Converter Function

Applications:

Targeted for Digital Video Professionals, Sophisticated End Users and OEMs
The AT72XUSB is an ideal solution for a number of applications such as:

- Development Tools.
- DVB to IP Gateway.
- DVB-C to DVB-ASI Conversion.
- MPEG-II Transport Stream Recording, Monitoring & Processing.
- Software Based MPEGII Decoders.

Specifications:

- On Board Buffer: 8 Mbytes.
- RF Tuner Connector: 75 Ohms IEC female Type.
- Loop Through Connector: 75 Ohms IEC male Type.
- Input Frequency Range: 54 MHz to 864 MHz.
- Input Level: -15dBmV to +15dBmV (QAM) & -80dBmV to 0dBmV (8-VSB).
- Channel Bandwidth: 6 MHz.
- Standards: DVB-C (ETS 300-429/ITU-T J83 Annex B) USA.
- Modulation Modes: 8VSB/64 QAM/256 QAM.
- DVB-ASI Connector: 75 Ohms BNC.
- Output Signal level: 1.0Vp-p nominal.
- Bit Rate Stability: +/- 25ppm.
- DVB-ASI Output Clock: 270 MHz.



Connections to AT72XUSB

IP Solutions Ltd. www.ip-solutions-ltd.com

Tel: +852 2850 8383 Fax: +852 2850 8182 E-mail: sales@ip-solutions-ltd.com

Rm1704, Lucky Commercial Centre, 103 Des Voeux Road West, Sheung Wan, Hong Kong